



Date: 11/22/09

Supersedes: 2/11/08

TECHNICAL DATA SHEET

VOONER VANEGARD® LIQUID RING COMPRESSOR

Specified, constructed, tested, and guaranteed by:

Vooner FloGard® Corporation

P.O. Box 240360, Charlotte, NC 28224-0360
4729 Stockholm Court, Charlotte, NC 28273

Telephone: (704) 552-9314
Toll Free: 1-800-345-7879
Telefax: (704) 554-8230

Model: VG20_-LC (DIN)

Type: Single stage rotor, cone shape ports, liquid ring compressor

Sealing liquid flow rate nominal: LPM = Kilowatts x 1.25
 Sealing liquid connection: 1" NPT
 Shaft sealing: Packing
 Bearing design: Double row spherical roller bearing, external, grease
 Lubricated, Type NSK 22220EAE4
 Shaft diameter, drive end: 92.1 mm
 Pump flange connections: 150 mm inlet, 125 mm outlet
 Manifold flange connections: 200 mm inlet, 150 mm outlet
 Approximate pump weight: 1490 kg

MATERIAL CONSTRUCTION FEATURES

Model	Rotor	Cones	Heads	Bearing Carrier	Housing	Shaft	Packing Gland, Studs, Nuts
A	Ductile Iron	Cast Iron	Cast Iron	Carbon Steel	Cast Iron	Carbon Steel	316 SS
C	304 SS	304 SS	Cast Iron	Carbon Steel	Cast Iron	410 HT SS	316 SS
XVE4	304 SS	304 SS	*316SS	Carbon Steel	**304L SS	410 HT SS	316 SS
XVE6	316 SS	316 SS	*316SS	Carbon Steel	**316L SS	410 HT SS	316 SS
XVS	304 SS	304 SS	*316SS	Carbon Steel	304 SS	410 HT SS	316 SS
SS4	304 SS	304 SS	304 SS	Carbon Steel	304 SS	316 SS	316 SS
SS6	316 SS	316 SS	316 SS	Carbon Steel	316 SS	316 SS	316 SS

(SS - cast stainless steel)

(HT - heat treated)

(*Replaceable 316 SS Wear Plates on cast heads)

(**Stainless Steel liner in cast iron housing)

(N/A - not available)